

Data Sheet for Article: LI146382--

# GILALED wall lamp, 3W, 3000K, 135lm, alu, silvergrey



## Technical Data

|                             |                         |
|-----------------------------|-------------------------|
| Cut-out size (mm)           | Ø102                    |
| Luminaire type              | Recessed wall luminaire |
| Mounting                    | recessed mounting wall  |
| Colour                      | Silver grey             |
| Material                    | Aluminum                |
| Manufacturer                | O3-SLV                  |
| Controller                  | LED driver              |
| Light source                | LED                     |
| Lamp holder                 | LED Platine             |
| Watt (W)                    | 3                       |
| System efficiency (lm/W)    | 45                      |
| Light colour                | warm white              |
| Colour temperature (K)      | 3000                    |
| Colour rendering index (Ra) | ≥80                     |
| Luminous flux (lm)          | 135                     |
| Number of lamps             | 1                       |
| Protection class            | III                     |
| Energy efficiency class     | A                       |

## Technical Data - continued

|                     |        |
|---------------------|--------|
| Swivel range (°)    | 190    |
| Mounting depth (mm) | 59     |
| Illuminant incl.    | yes    |
| Diameter (mm)       | 112    |
| ØxH mm              | 112x63 |
| Cut-out size mm     | Ø102   |

## Article Table

| DESCRIPTION                                          | Order No. |
|------------------------------------------------------|-----------|
| GILALED wall lamp, 3W, 3000K, 135lm, alu, silvergrey | LI146382  |
| <b>Optional Accessories</b>                          |           |
| LED driver, 3W, 700mA, incl. stress relief           | LI464200  |