

Data Sheet for Article: LI147326--

KALU 3 QPAR ceiling light, alu brushed. ES111, max. 3x75W



Product Details

Das puristische Grunddesign der KALU Deckenleuchte ist ein Garant für vollkommen freie Ausrichtung der Leuchtenköpfe, wahlweise bestückt mit Halogen oder passenden LED ES 111 Leuchtmitteln. Die Dimmbarkeit der Leuchte eröffnet Ihnen weitere Einsatzmöglichkeiten. Erhältlich in mehreren Farbversionen wird die KALU Deckenleuchte fertig für den direkten Anschluss an 230V Netzspannung geliefert.

Technical Data

Dimmable	yes Depending on light source
Protection class	I
Luminaire type	surface mounted ceiling luminaire
Light source	ES111 main voltage halogen reflector lamp LED Retrofit
Illuminant incl.	no
Number of lamps	3
Lamp holder	GU10
Swivel range (°)	90
Power (W)	3x75

Technical Data - continued

Operating voltage AC (V)	230
Mounting	surface mounting ceiling
Colour	Aluminum brushed
Material	Aluminum
Length (mm)	450
Width (mm)	90
Height (mm)	180
Optional Accessories	LI1005274-;LI1005282-;LI1005298-
LxWxH mm	450x90x180

Article Table

DESCRIPTION	Order No.
KALU 3 QPAR ceiling light, alu brushed. ES111, max. 3x75W	LI147326
Optional Accessories	
QPAR111 GU10, LED lamp transparent 8W 2,7K CRI90 38° Non-directional LED high voltage lamp	LI1005274
QPAR111 GU10, LED lamp silver 12,5W 4000K CRI90 30° Non-directional LED high voltage lamp	LI1005282
LED-Illuminance 12W, 680lm, 930,55°, GU10, IP20, aluminium LED main voltage illuminant gerichtet	LI1005298