

Data Sheet for Article: LI151951--

DOWNUNDER PUR 120 3,6W LED, 3000K, 80x120, white

Recessed wall luminaire



Technical Data

Manufacturer	03-SLV
Watt (W)	3,50
Power (W)	3,50
Luminous flux (lm)	265
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Service life	30.000h
Protection class	III
IP Rating	IP20
Energy efficiency class	A
Luminaire type	Recessed wall luminaire
Light source	LED
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine
System efficiency (lm/W)	76

Technical Data - continued

Controller	LED driver
Mounting	recessed wall mounting
Mounting depth (mm)	35
Colour	White
Material	Steel Aluminum
Optional Accessories	LI1002803-;LI151961--;LI464109--

Article Table

DESCRIPTION	Order No.
DOWNUNDER PUR 120 3,6W LED, 3000K, 80x120, white Recessed wall luminaire	LI151951
Optional Accessories	
LED driver 15W 350mA dimmable	LI1002803
Mounting frame for DOWNUNDER PUR 80x120, angular	LI151961
LED driver, 8VA, 350 mA, incl. stress relief	LI464109