


Data Sheet for Article: LI158663--

# LED PANEL ROUND 60, 3000K, round, matt white



## Technical Data

|                             |                    |
|-----------------------------|--------------------|
| Net height (mm)             | 40,00              |
| Net diameter (mm)           | 600,00             |
| Net weight (kg)             | 2,51               |
| Cut-out size (mm)           | Ø590               |
| Luminaire type              | pendulum luminaire |
| Mounting                    | Pendant            |
| Colour                      | White              |
| Material                    | Aluminum           |
| Manufacturer                | O3-SLV             |
| Emission angle (°)          | 120                |
| Light source                | SMD LED            |
| Lamp holder                 | LED Platine        |
| Watt (W)                    | 40                 |
| System efficiency (lm/W)    | 66                 |
| Light colour                | warm white         |
| Colour temperature (K)      | 3000               |
| Colour rendering index (Ra) | ≥80                |
| Luminous flux (lm)          | 2630               |

## Technical Data - continued

|                         |              |
|-------------------------|--------------|
| Number of lamps         | 1            |
| Live time               | 30.000h      |
| Protection class        | III          |
| Energy efficiency class | A++   A+   A |
| Mounting depth (mm)     | 60           |
| Illuminant incl.        | yes          |
| ØxH mm                  | 600x40       |
| Cut-out size mm         | Ø590         |

## Article Table

| DESCRIPTION                                                                      | Order No. |
|----------------------------------------------------------------------------------|-----------|
| LED PANEL ROUND 60, 3000K, round, matt white                                     | LI158663  |
| <b>Optional Accessories</b>                                                      |           |
| TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable<br>inkl. Cable relief | LI464032  |
| LED-Driver, 40W, 1000mA, incl. strain relief                                     | LI464170  |
| LED-Driver, 40W, 1000mA, incl. strain relief, dimmable                           | LI464176  |
| LED Driver 40W, 1050mA, dimmable                                                 | LI464804  |
| 3-way connection box, IP20, Quick Fix                                            | LID15379  |