


Data Sheet for Article: LI158713--

I-VIDUAL LED PANEL for ceiling grid 625x625, 3000K, white



Technical Data

Net length (mm)	617,00
Net width (mm)	617,00
Net height (mm)	13,00
Net weight (kg)	4,31
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	White
Material	Acryl Aluminum
Manufacturer	03-SLV
Emission angle (°)	110
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	40
System efficiency (lm/W)	73
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80

Technical Data - continued

Luminous flux (lm)	2900
Number of lamps	2
Live time	30000
Protection class	III
Energy efficiency class	A++ A+ A
Mounting depth (mm)	50
Illuminant incl.	yes
LxWxH mm	617x617x13

Article Table

DESCRIPTION	Order No.
I-VIDUAL LED PANEL for ceiling grid 625x625, 3000K, white	LI158713
Optional Accessories	
Universal-frame for LED-Panel, 620x620mm, white	LI158772
INSTALLATION FRAME, silver-grey, L/W 62.5/62.5 cm for I-VIDUAL LED panel	LI158774
rosette, 10,3cm x 22cm x 5,1cm, matt white	LI158791
Suspension set for LED Panel	LI158799
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable inkl. Cable relief	LI464032
LED-Driver, 40W, 1000mA, incl. strain relief	LI464170
LED-Driver, 40W, 1000mA, incl. strain relief, dimmable	LI464176