

Data Sheet for Article: LI158804--

I-VIDUAL LED Panel for grid ceilings, 600x600mm, UGR<22, 4000K

white



Technical Data

Net length (mm)	595,00
Net width (mm)	595,00
Net height (mm)	13,00
Net weight (kg)	4,35
Manufacturer	03-SLV
Glare factor (UGR)	<22
Input voltage AC (V)	1000mA 1050mA
Lamp holder	LED Platine
LxWxH mm	595x595x13

Article Table

DESCRIPTION	Order No.
I-VIDUAL LED Panel for grid ceilings, 600x600mm, UGR<22, 4000K white	LI158804
Optional Accessories	
Universal-frame for LED-Panel, 595x595mm, white	LI158762
INSTALLATION FRAME, silver-grey, L/W 60.5/60.5 cm for I-VIDUAL LED panel	LI158764
rosette, 10,3cm x 22cm x 5,1cm, matt white	LI158791
Suspension set for LED Panel	LI158799
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable inkl. Cable relief	LI464032
LED-Driver, 40W, 1000mA, incl. strain relief	LI464170
LED-Driver, 40W, 1000mA, incl. strain relief, dimmable	LI464176