

Data Sheet for Article: LI158823--

# I-VIDUAL LED Panel for grid ceilings, 600x600mm, UGR<22, 3000K

silver



## Technical Data

|                    |             |
|--------------------|-------------|
| Net length (mm)    | 595,00      |
| Net width (mm)     | 595,00      |
| Net height (mm)    | 13,00       |
| Net weight (kg)    | 4,30        |
| Manufacturer       | 03-SLV      |
| Glare factor (UGR) | <22         |
| Lamp holder        | LED Platine |
| LxWxH mm           | 595x595x13  |

## Article Table

| DESCRIPTION                                                                      | Order No. |
|----------------------------------------------------------------------------------|-----------|
| I-VIDUAL LED Panel for grid ceilings, 600x600mm, UGR<22, 3000K<br>silver         | LI158823  |
| <b>Optional Accessories</b>                                                      |           |
| Universal-frame for LED-Panel, 595x595mm, white                                  | LI158762  |
| INSTALLATION FRAME, silver-grey, L/W 60.5/60.5 cm<br>for I-VIDUAL LED panel      | LI158764  |
| rosette, 10,3cm x 22cm x 5,1cm, matt white                                       | LI158791  |
| Suspension set for LED Panel                                                     | LI158799  |
| TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable<br>inkl. Cable relief | LI464032  |
| LED-Driver, 40W, 1000mA, incl. strain relief                                     | LI464170  |
| LED-Driver, 40W, 1000mA, incl. strain relief, dimmable                           | LI464176  |