


Data Sheet for Article: LI161291--

CONTONE IP44, 16W, 890lm, 2000-3000K dimm, round, white



Light distribution curve



Product Details

Mit der CONTONE Deckeneinbauleuchte können Sie Ihre Lichtstimmung individuell bestimmen. Beim Dimmen des integrierten Premium COB LED Moduls verändert sich die Lichtfarbe von 3000K auf 2000K und zeigt beim Abdimmen den gleichen Effekt wie Glühfaden-Leuchtmittel. Der elektrische Anschluss erfolgt durch den verbauten LED Treiber direkt an 230V Netzspannung.

Technical Data

Luminous flux (lm)	890
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90

Technical Data - continued

Service life	40.000h
Dimmable	yes trailing edge dimmable (C)
IP Rating	IP44
Luminaire type	Recessed ceiling luminaire Recessed wall luminaire
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	30
System efficiency (lm/W)	56
Power (W)	16
Controller	LED driver
Operating voltage AC (V)	220-240
Mounting	recessed wall mounting recessed mounting ceiling
Cut-out size (mm)	Ø 82
Mounting depth (mm)	135
Colour	White
Material	Aluminum
Length (mm)	92
Width (mm)	92
Height (mm)	140
Diameter (mm)	92
Weight (kg)	0,32
LxWxH mm	92x92x140
ØxH mm	92x140
Cut-out size mm	Ø 82

DESCRIPTION	Order No.
CONTONE IP44, 16W, 890lm, 2000-3000K dimm, round, white	LI161291