

Data Sheet for Article: LI29001242

# Led Panel 33W, 4000lm, 840, 1197x297mm, 1050mA, excl. Driver



## Technical Data

|                               |                           |
|-------------------------------|---------------------------|
| Net length (mm)               | 1.197,00                  |
| Net width (mm)                | 297,00                    |
| Net height (mm)               | 9,00                      |
| Net weight (kg)               | 3,70                      |
| Min. ambient temperature (°C) | -20                       |
| Max. ambient temperature (°C) | 40                        |
| Mounting                      | recessed mounting ceiling |
| Colour                        | White                     |
| Material                      | Plastic<br>Metal          |
| Manufacturer                  | 02-Schrack                |
| Beam angle (°)                | 80                        |
| Glare factor (UGR)            | <19                       |
| Operating voltage DC (V)      | 30-34                     |
| Operation current mA (mA)     | 1050                      |
| Light source                  | SMD LED                   |
| Lamp holder                   | LED Platine               |
| Watt (W)                      | 42                        |

## Technical Data - continued

|                             |               |
|-----------------------------|---------------|
| System efficiency (lm/W)    | 105           |
| Light colour                | neutral white |
| Colour temperature (K)      | 4000          |
| Colour rendering index (Ra) | ≥85           |
| Luminous flux (lm)          | 4000          |
| Live time                   | 50.000h       |
| Dimmable                    | yes           |
| Protection class            | 3             |
| IP Rating                   | IP20          |
| LxWxH mm                    | 1197x297x9    |

## Article Table

| DESCRIPTION                                                  | Order No.  |
|--------------------------------------------------------------|------------|
| Led Panel 33W, 4000lm, 840, 1197x297mm, 1050mA, excl. Driver | LI29001242 |
| <b>Optional Accessories</b>                                  |            |
| Led Driver 47W, 100-240V CC 1050mA 30-42V DC                 | LI19001000 |
| Led Driver 46W, 220-240V CC 1050mA 21-48V DC Dali            | LI29001075 |
| Led Driver 47W, 220-240V CC 1050mA 4-48V DC 1-10V            | LI29001076 |
| Led Panel Surface Mounting Kit for 1197x297mm Serie Ledon    | LI29001094 |
| Led Panel Wall Bracket for Surface Mounting Kit Serie Ledon  | LI29001097 |
| Led Panel Suspension Kit 4x1M, Serie Ledon                   | LI29001064 |
| Led Panel Suspension Kit 4x2M, Serie Ledon                   | LI29001096 |
| Led Backlight 120 800lm, 110°, 840, 1050mA                   | LI29001142 |
| 3-way connection box, IP20, Quick Fix                        | LID15379   |