


Data Sheet for Article: LI2J67124H

LINDA LED PC 1x24W, 4000K, 3914lm, IP65, PC II grey, L=1270mm

moisture-proof diffuser luminaire



Light distribution curve



Technical Data

Net length (mm)	1.270,00
Net width (mm)	100,00
Net height (mm)	100,00
Net weight (kg)	1,90
Min. ambient temperature (°C)	-20

Technical Data - continued

Max. ambient temperature (°C)	35
Luminaire type	Moisture proof luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	RAL 7035 (grau)
Material	Polycarbonate
Cover	transparent
Glare factor (UGR)	<22
Controller	LED driver
Operating voltage AC (V)	230
Lamp holder	LED Platine
Power of system (W)	28
System efficiency (lm/W)	145
Power (W)	1x24
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	3
Luminous flux (lm)	4065
Number of lamps	1
Service life	L80/B10 = 100.000h
Dimmable	no
Protection class	II
IP Rating	IP66
Shock strength	IK10
Illuminant incl.	yes
LxWxH mm	1270x100x100

Article Table

DESCRIPTION	Order No.
LINDA LED PC 1x24W, 4000K, 3914lm, IP65, PC II grey, L=1270mm moisture-proof diffuser luminaire	LI2J67124H
Optional Accessories	
LINDA suspension hook for chain (old) hooks for Linda with old mounting brackets	LIMMMO2700