

Data Sheet for Article: LI2JL58808

Linda LED Transparent 1x24W, 4000K, 3935lm, IP65, L=1270mm

moisture-proof diffuser luminaire



Technical Data

Net length (mm)	1.270,00
Net width (mm)	100,00
Net height (mm)	100,00
Net weight (kg)	1,90
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Luminaire type	Moisture proof luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Transparent
Material	Polycarbonate
Cover	transparent
Glare factor (UGR)	<22

Technical Data - continued

Controller	LED driver
Operating voltage AC (V)	230
Lamp holder	LED Platine
Power of system (W)	28
System efficiency (lm/W)	129
Power (W)	24
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	3
Luminous flux (lm)	3935
Number of lamps	1
Service life	80.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP65
Shock strength	IK10
Illuminant incl.	yes
LxWxH mm	1270x100x100

Article Table

DESCRIPTION	Order No.
Linda LED Transparent 1x24W, 4000K, 3935lm, IP65, L=1270mm moisture-proof diffuser luminaire	LI2JL58808
Optional Accessories	
LINDA Spare cover PC for single luminaires, L=1270mm	LIC4LD1S00
Clip Inox for LINDA	LICVVID670
LINDA mounting spring, Clips Inox (old)	LI2JLI0304
Linda suspension hook for chain	LI2JLI0484