

Data Sheet for Article: LI2JL58810

Linda LED Transparent 1x30W, 4000K, 4925lm, IP65, L=1570mm

moisture-proof diffuser luminaire



Technical Data

Net length (mm)	1.570,00
Net width (mm)	100,00
Net height (mm)	100,00
Net weight (kg)	2,40
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Luminaire type	Moisture proof luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Transparent
Material	Polycarbonate
Cover	transparent
Manufacturer	01-Schrack-Trinity

Technical Data - continued

Glare factor (UGR)	<22
Controller	LED driver
Operating voltage AC (V)	230
Lamp holder	LED Platine
Watt (W)	30
Power of system (W)	34
System efficiency (lm/W)	133
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	4925
Number of lamps	1
Service life	80.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP65
Shock strength	IK10
Illuminant incl.	yes
LxWxH mm	1570x100x100

Article Table

DESCRIPTION	Order No.
Linda LED Transparent 1x30W, 4000K, 4925lm, IP65, L=1570mm moisture-proof diffuser luminaire	LI2JL58810
Optional Accessories	
Linda Spare cover for single luminaires, L=1570mm	LIC6LD1S00
Clip Inox for Linda	LICVVID670
Linda mounting spring, Clips Inox	LI2JLI0304
Linda suspension hook for chain	LI2JLI0484