


Data Sheet for Article: LI38OF0076

OFFICE II FSL LED 76W 10655lm, 840, D/I, dimm, LS/PD, anodized

LS/PD - light sensor and presence detector, direct/indirect, Lumenoutput direkt 6230lm / indirekt 3990lm



Light distribution curve



Technical Data

Net length (mm)	640,00
Net width (mm)	310,00
Net height (mm)	1.960,00
Net weight (kg)	17,50

Technical Data - continued

Min. ambient temperature (°C)	5
Max. ambient temperature (°C)	35
Luminaire type	Free standing luminaire
Mounting	Mobil
Colour	Anodized
Material	Aluminum
Cover	mikroprismatic
Glare factor (UGR)	<19
Controller	LED driver
Operating voltage AC (V)	230
Lamp holder	LED Platine
Power of system (W)	80
System efficiency (lm/W)	140
Power (W)	76
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	10655
Luminous flux luminaire (lm)	10200
Number of lamps	1
Service life	50.000h / L70 / B50
Dimmable	DALI yes
Protection class	I
IP Rating	IP20
Illuminant incl.	yes
LxWxH mm	640x310x1960

Article Table

DESCRIPTION	Order No.
OFFICE II FSL LED 76W 10655lm,840,D/I, dimm, LS/PD,anodized	LI38OF0076
LS/PD - light sensor and presence detector, direct/indirect, Lumenoutput direkt 6230lm / indirekt 3990lm	
Optional Accessories	
Flush-mounted Dimmer inbox for Dali Ballasts or Drivers	EHDALIDIM
For push button control	