

Data Sheet for Article: LI43518415

# RL-T8 18 S 7,5W 830 1000lm G13 190° matt UN L-600mm

LED retrofit tube for 230V direct connection, operation with a magnetic ballast or suitable ECG



## Technical Data

|                                 |            |
|---------------------------------|------------|
| Net length (mm)                 | 600,00     |
| Net diameter (mm)               | 28,00      |
| Net weight (kg)                 | 0,14       |
| Min. ambient temperature (°C)   | -20        |
| Max. ambient temperature (°C)   | 50         |
| Make-up                         | Röhrenform |
| Beam angle (°)                  | 160        |
| Operating voltage AC (V)        | 220 - 240  |
| Operation current mA (mA)       | 45         |
| Socket                          | G13        |
| Power (W)                       | 7,50       |
| Light colour                    | warm white |
| Colour temperature (K)          | 3000       |
| Colour rendering index (Ra)     | ≥80        |
| Colour stability MacAdam (sdcm) | ≤ 6        |
| Luminous flux (lm)              | 1000       |
| Service life                    | 50.000h    |

## Technical Data - continued

|               |      |
|---------------|------|
| Dimmable      | no   |
| IP Rating     | IP20 |
| EEC           | E    |
| Diameter (mm) | 28   |

| DESCRIPTION                                                                                                                                            | Order No.  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| RL-T8 18 S 7,5W 830 1000lm G13 190° matt UN L-600mm<br>LED retrofit tube for 230V direct connection, operation with a magnetic ballast or suitable ECG | LI43518415 |