

Data Sheet for Article: LI43518499

# RL-T5 54 HO 26W 230V 160° 830 3600lm G5 UN L=1149mm

T5 retrofit tube for operation with suitable ECG or at 230V



## Technical Data

|                             |            |
|-----------------------------|------------|
| Make-up                     | Röhrenform |
| Beam angle (°)              | 160        |
| Operating voltage AC (V)    | 220 - 240  |
| Version                     | matt       |
| Operation current mA (mA)   | 120        |
| Socket                      | G5         |
| Watt (W)                    | 26         |
| Power (W)                   | 26         |
| Light colour                | warm white |
| Colour temperature (K)      | 3000       |
| Colour rendering index (Ra) | ≥80        |
| Luminous flux (lm)          | 3600       |
| Service life                | 60.000h    |
| Dimmable                    | no         |
| IP Rating                   | IP20       |
| Diameter (mm)               | 21         |
| Power Factor                | ≥ 0.90     |

## Technical Data - continued

Colour stability MacAdam (sdcm)

| ≤ 6

## Article Table

| DESCRIPTION                                                                                                        | Order No.  |
|--------------------------------------------------------------------------------------------------------------------|------------|
| RL-T5 54 HO 26W 230V 160° 830 3600lm G5 UN L=1149mm<br>T5 retrofit tube for operation with suitable ECG or at 230V | LI43518499 |