

Data Sheet for Article: LI552142--

FlexLED Roll 24V, 40W, 3000K, 3m, 60LED/m



Product Details

Rückseite mit Klebeband ausgestattet, Trennbar alle 10 cm. Betrieb ausschließlich mit 24V= Netzteilen, Ab 300 cm muss neu eingespeist werden

Technical Data

Manufacturer	03-SLV
Luminous flux (lm)	1020
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Protection class	III
Luminaire type	LED Strip
Light source	SMD LED
Illuminant incl.	yes
Beam angle (°)	120
Power (W)	40
Operating voltage DC (V)	24
Mounting	surface mounting wall
Optional Accessories	LI470544--,LI550413--,LI550416--,LI550560--,LI550570--

Technical Data - continued

LxWxH mm

3000x10x2

Article Table

DESCRIPTION	Order No.
FlexLED Roll 24V, 40W, 3000K, 3m, 60LED/m	LI552142
Optional Accessories	
LED power unit, 36W, 24V	LI470544
Feed in for Flexled Roll 12V up to 10mm width, length = 30cm	LI550413
Direct connector for Flexled Roll 12V up to 10mm width, 2pcs	LI550416
LED strip clip connector	LI550560
Soldering edges 90° for FLEXLED ROLL, max.2A, 12V/24V, 2 pcs	LI550570