


Data Sheet for Article: LI60111610

# ALSF 1560 ML BASIC 55/43W 6600/5100lm 840 IP54 PMMA opal wh



## Light distribution curve




## Technical Data

|                               |          |
|-------------------------------|----------|
| Net length (mm)               | 1.560,00 |
| Net width (mm)                | 105,00   |
| Net height (mm)               | 95,00    |
| Net weight (kg)               | 2,92     |
| Min. ambient temperature (°C) | -20      |
| Max. ambient temperature (°C) | 25       |
| Colour                        | White    |
| Material                      | PMMA     |
| Beam angle (°)                | 120      |
| Operating voltage AC (V)      | 220-240  |
| System efficiency (lm/W)      | 120      |

## Technical Data - continued

|                                 |             |
|---------------------------------|-------------|
| Power (W)                       | 55          |
| Colour temperature (K)          | 4000        |
| Colour rendering index (Ra)     | 80          |
| Colour stability MacAdam (sdcm) | 3           |
| Luminous flux (lm)              | 6600        |
| Service life                    | 30000       |
| Dimmable                        | no          |
| Protection class                | I           |
| IP Rating                       | IP54        |
| Shock strength                  | IK02        |
| LxWxH mm                        | 1560x105x95 |

### Dimensioned drawing: ALSF 1560 ML BASIC 55/43W 6600/5100lm 840 IP54 PMMA opal wh



| DESCRIPTION                                                 | Order No.  |
|-------------------------------------------------------------|------------|
| ALSF 1560 ML BASIC 55/43W 6600/5100lm 840 IP54 PMMA opal wh | LI60111610 |