


Data Sheet for Article: LI99001674

SARM LED 18W 3000K, 2400lm, Ra>80, white, ECG, L=1234

Ceiling mounted luminaire with matt louver



Light distribution curve



Technical Data

Net length (mm)	1.234,00
Net width (mm)	118,00
Net height (mm)	58,00
Net weight (kg)	3,80
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Luminaire type	pendulum luminaire surface mounted ceiling luminaire

Technical Data - continued

Mounting	surface mounting ceiling pendant
Colour	RAL 9003 (white)
Material	Aluminum sheetsteel
Cover	parabolic matt
Manufacturer	01-Schrack-Trinity
Glare factor (UGR)	<19 / <22
Controller	ECG
Operating voltage AC (V)	220-240
Colour stability MacAdam (sdcm)	3
Lamp holder	LED Platine
System efficiency (lm/W)	107
Power (W)	21
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	2250
Number of lamps	1
Service life	50.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP20
Illuminant incl.	yes

Article Table

DESCRIPTION	Order No.
SARM LED 18W 3000K, 2400lm, Ra>80, white, ECG, L=1234 Ceiling mounted luminaire with matt louver	LI99001674
Optional Accessories	
Suspension set with square ceiling rose für SAR LED, white without cable, cord length 1500mm	LI99001721
Suspension set with round ceiling rose für SAR LED, white without cable, cord length 1500mm	LI99001722