



Data Sheet for Article: LI99001706

SERM LED 112 L 1x48W 4000K 6550lm Ra>80 white ECG

Recessed luminare for plasterboard ceilings, with bracket



Light distribution curve



Technical Data

Net length (mm)	1.500,00
Net width (mm)	112,00
Net height (mm)	61,00
Net weight (kg)	2,80
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Cut-out size (mm)	100x1480
Luminaire type	Recessed ceiling luminaire

Technical Data - continued

Mounting	recessed mounting ceiling
Colour	RAL 9003 (white)
Material	sheetsteel
Manufacturer	01-Schrack-Trinity
Glare factor (UGR)	<20
Controller	ECG
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
Watt (W)	48
System efficiency (lm/W)	139
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	6550
Service life	100.000h / L90 / B10
Dimmable	no
Protection class	I
IP Rating	IP20
Illuminant incl.	yes
LxWxH mm	1500x112x61
Cut-out size mm	100x1480

Article Table

DESCRIPTION	Order No.
SERM LED 112 L 1x48W 4000K 6550lm Ra>80 white ECG	LI99001706
Recessed luminire for plasterboard ceilings, with bracket	