


Data Sheet for Article: LI99001709


SERM LED 112 M 1x16W 3000K 2200lm

Ra>80 UGR<19 white DALI

Recessed luminare for plasterboard ceilings, with bracket



Light distribution curve



Technical Data

Net length (mm)	1.200,00
Net width (mm)	112,00
Net height (mm)	61,00
Net weight (kg)	2,30
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Cut-out size (mm)	100x1180
Luminaire type	Recessed ceiling luminaire

Technical Data - continued

Mounting	recessed mounting ceiling
Colour	RAL 9003 (white)
Material	sheetsteel
Manufacturer	01-Schrack-Trinity
Glare factor (UGR)	<19
Controller	EVG DALI
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
Watt (W)	16
System efficiency (lm/W)	105
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	2200
Service life	100.000h / L90 / B10
Dimmable	DALI
Protection class	I
IP Rating	IP20
Illuminant incl.	yes
LxWxH mm	1200x112x61
Cut-out size mm	100x1180

Article Table

DESCRIPTION	Order No.
SERM LED 112 M 1x16W 3000K 2200lm Ra>80 UGR<19 white DALI Recessed luminire for plasterboard ceilings, with bracket	LI99001709