


Data Sheet for Article: LI99001748

# Lano PRO LED 33W, 3800lm, 840, microprismatic, ECG, White

LED Panel M625 Ra >80, UGR <19, 220-240V, SKII, IP20, aluminium



## Light distribution curve



## Technical Data

|                               |                           |
|-------------------------------|---------------------------|
| Net length (mm)               | 620,00                    |
| Net width (mm)                | 620,00                    |
| Net height (mm)               | 10,00                     |
| Net weight (kg)               | 4,00                      |
| Min. ambient temperature (°C) | -20                       |
| Max. ambient temperature (°C) | 35                        |
| Mounting                      | recessed mounting ceiling |
| Colour                        | RAL 9016 (white)          |
| Material                      | Aluminum<br>PC            |
| Cover                         | mikroprismatic            |

## Technical Data - continued

|                             |                     |
|-----------------------------|---------------------|
| Manufacturer                | 02-Schrack          |
| Emission angle (°)          | 120                 |
| Glare factor (UGR)          | <19                 |
| Controller                  | LED driver          |
| Operating voltage AC (V)    | 220-240             |
| Light source                | LED                 |
| Lamp holder                 | LED Platine         |
| Watt (W)                    | 33                  |
| System efficiency (lm/W)    | 115                 |
| Light colour                | neutral white       |
| Colour temperature (K)      | 4000                |
| Colour rendering index (Ra) | 80                  |
| Luminous flux (lm)          | 3800                |
| Live time                   | 50.000h / L80 / B10 |
| Dimmable                    | no                  |
| IP Rating                   | IP20/40             |
| LxWxH mm                    | 620x620x10          |

## Article Table

| DESCRIPTION                                                     | Order No.  |
|-----------------------------------------------------------------|------------|
| Lano PRO LED 33W, 3800lm, 840, microprismatic, ECG, White       | LI99001748 |
| LED Panel M625 Ra >80, UGR <19, 220-240V, SKII, IP20, aluminium |            |
| <b>Optional Accessories</b>                                     |            |
| 3-way connection box, IP20, Quick Fix                           | LID15379   |