


Data Sheet for Article: LID10229--

Sutil Round LED Panel 12W, 3000K, 745lm, Ø178mm, white **€ECONOMY**




Technical Data

Cut-out size (mm)	Ø165
Luminaire type	LED Panel
Mounting	recessed mounting ceiling
Colour	White
Material	Aluminum
Cover	opal
Manufacturer	O6-One Light
Emission angle (°)	120
Controller	LED driver
Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Output voltage DC (V)	8,5-10,5
Output current (A)	0,5
Light source	SMD LED
Watt (W)	12

Technical Data - continued

Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	745
Number of lamps	1
Live time (h)	30000
Dimmable	yes with optional, dimmable driver
Protection class	II
IP Rating	IP40
Energy efficiency class	A
Mounting depth (mm)	40
Illuminant incl.	yes
ØxH mm	178x14
Cut-out size mm	Ø165

Dimensioned drawing: Sutil Round LED Panel 12W, 3000K, 745lm, Ø178mm, white



Article Table

DESCRIPTION	Order No.
Sutil Round LED Panel 12W, 3000K, 745lm, Ø178mm, white	LID10229
Optional Accessories	
Optional dimmable LED driver for Sutil Round LED 12W	LID13346