


Data Sheet for Article: LID10251--

Dingo Small LED downlight 20W, 3000K, 1500lm, dimm, white **ECONOMY**




Technical Data

Cut-out size (mm)	Ø150
Luminaire type	downlight
Mounting	recessed mounting ceiling
Colour	White
Material	Aluminum Glass
Cover	transparent
Emission angle (°)	100
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	230
Output voltage AC (V)	35-42
Output current (A)	0,50
Light source	COB LED
Lamp holder	LED Platine

Technical Data - continued

Watt (W)	20
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	1500
Number of lamps	1
Live time (h)	35000
Dimmable	TRIAC
Protection class	II
IP Rating	IP53
Energy efficiency class	A
Mounting depth (mm)	170
Illuminant incl.	yes
ØxH mm	164x140
Cut-out size mm	Ø150

Dimensioned drawing: Dingo Small LED downlight 20W, 3000K, 1500lm, dimm, white



Article Table

DESCRIPTION	Order No.
Dingo Small LED downlight 20W, 3000K, 1500lm, dimm, white	LID10251