




Data Sheet for Article: LID10262--

Dingo Large LED downlight 30W, 4500K, 2200lm, dimm, grey **€CONOMY**



Light distribution curve




Technical Data

Cut-out size (mm)	Ø210
Luminaire type	downlight
Mounting	recessed mounting ceiling
Colour	Gray
Material	Aluminum Glass
Cover	transparent
Emission angle (°)	100
Controller	LED driver

Technical Data - continued

Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Output voltage AC (V)	35-42
Output current (A)	0,70
Light source	COB LED
Watt (W)	30
Light colour	neutral white
Colour temperature (K)	4500
Colour rendering index (Ra)	≥80
Luminous flux (lm)	2200
Number of lamps	1
Live time (h)	35000
Dimmable	TRIAC
Appliance class	II
IP Rating	IP53
Energy efficiency class	A
Mounting depth (mm)	210
Illuminant incl.	yes
ØxH mm	242x180
Cut-out size mm	Ø210

Dimensioned drawing: Dingo Large LED downlight 30W, 4500K, 2200lm, dimm, grey



Article Table

DESCRIPTION	Order No.
Dingo Large LED downlight 30W, 4500K, 2200lm, dimm, grey	LID10262