



Data Sheet for Article: LID10911 --

Sutil Quadro LED, 10W, 3000K, 750lm, 200x200mm, IP44, grey **€ECONOMY**



Light distribution curve




Technical Data

Cut-out size (mm)	185x185
Luminaire type	LED Panel
Mounting	recessed mounting wall recessed mounting ceiling
Colour	Gray
Material	Aluminum
Cover	opal
Emission angle (°)	120
Controller	LED driver

Technical Data - continued

Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Output voltage AC (V)	12-25
Output current (A)	0,54
Light source	SMD LED
Watt (W)	10
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	750
Number of lamps	1
Live time (h)	20000
Protection class	II
IP Rating	IP44
Energy efficiency class	A
Mounting depth (mm)	40
Illuminant incl.	yes
LxWxH mm	200x200x12
Cut-out size mm	185x185

Dimensioned drawing: Sutil Quadro LED, 10W, 3000K, 750lm, 200x200mm, IP44, grey



Article Table

DESCRIPTION	Order No.
Sutil Quadro LED, 10W, 3000K, 750lm, 200x200mm, IP44, grey	LID10911