


Data Sheet for Article: LID12034--

7028A/AN/W ANTHRACITE 10w WW IP65

100-240V **€ECONOMY**

21 INDUSTRIAL & FLDS



Product Details

10W COB LED Slim floodlight, IP65. Supplied with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.




Technical Data

Net length (mm)	157,00
Net width (mm)	121,00
Net height (mm)	121,00
Netto depth (mm)	52,00
Net weight (kg)	0,92
Luminaire type	Floodlight
Mounting	surface mounting ceiling surface mounting wall floor mounting mast mounting

Technical Data - continued

Colour	Anthracite
Material	Die-cast aluminum
Cover	transparent
Beam angle (°)	120
Controller	LED driver
Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Operation current mA (mA)	300
Lamp holder	LED Platine
System efficiency (lm/W)	70
Power (W)	10
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥70
Luminous flux (lm)	700
Number of lamps	1
Dimmable	no
Protection class	I
IP Rating	IP65
Swivel range (°)	180
Illuminant incl.	yes
LxWxH mm	157x121x121
Length (mm)	157
Width (mm)	121
Height (mm)	121

Dimensioned drawing: 7028A/AN/W ANTHRACITE 10w WW IP65 100-240V



DESCRIPTION	Order No.
7028A/AN/W ANTHRACITE 10w WW IP65 100-240V 21 INDUSTRIAL & FLDS	LID12034