


Data Sheet for Article: LID12356--

Marra LED Strip 14,4W/m 60LEDs/m 900lm/m 6000K 24VDC IP68 €ECONOMY

LED Flexstrip, dimmable, 5 Meter Roll



Technical Data

Luminaire type	LED Strip
Mounting	surface mounting ceiling surface mounting wall floor mounting
Material	PVC
Beam angle (°)	120
Operating voltage AC (V)	24
Operating voltage DC (V)	24
Light source	SMD LED
Watt/m (W/m)	14,40
Light colour	daylight
Colour temperature (K)	6000
Colour rendering index (Ra)	≥80
luminous flux/m (lm/m)	900

Technical Data - continued

Service life	50.000h
Dimmable	yes
Protection class	III
IP Rating	IP54
Illuminant incl.	yes
LxWxH mm	5000x12x5

Dimensioned drawing: Marra LED Strip 14,4W/m 60LEDs/m 900lm/m 6000K 24VDC IP68



Article Table

DESCRIPTION	Order No.
Marra LED Strip 14,4W/m 60LEDs/m 900lm/m 6000K 24VDC IP68 LED Flexstrip, dimmable, 5 Meter Roll	LID12356
Optional Accessories	
Aluminium profile 7906/AL+PMMA opal square diffuser, 2 meters Suitable for LED Strips 7820, 7821, 7825, 7830, 7831, 7835, 7820W, 7830W, 7831W, 7835W	LID13861
Triange aluminium profile 7908/AL,+PC opal diffuser, 2 meters Suitable for LED Strips 7820, 7821, 7825, 7830, 7831, 7835, 7870, 7875, 7820W, 7830W, 7831W, 7835W	LID13862
Aluminium recessed profile 7912R/AL+PC opal diffuser, 2 meters Suitable for LED Strips 7820, 7821, 7825, 7830, 7831, 7835, 7870, 7875, 7820W, 7830W, 7831W, 7835W	LID13865
7827, MOUNTING CLIP for 7830W / 7831W	LID13413