


Data Sheet for Article: LID12400--

7870/W LED STRIP 24V DC WW 5m ROLL

19,2W/m IP20 €CONOMY

LED Flexstrip, dimmable, 5 Meter Roll; 08 STRIPS & PROFILES



Product Details

Flexible LED light strip, with SMD2216 LEDs, 238LEDs/meter, 19,2W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 2,95cm (7-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.



Technical Data

Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Service life	50.000h
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
EEC	F

Technical Data - continued

Energy efficiency class	F
Luminaire type	LED Strip
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	90
Controller	Needs to be ordered separately
Operating voltage DC (V)	24
Input voltage DC (V)	24
Mounting	surface mounting ceiling surface mounting wall floor mounting
Material	PVC
Length (mm)	5000
Width (mm)	10
Height (mm)	3
Optional Accessories	LID 14125--
LxWxH mm	5000x10x3
luminous flux/m (lm/m)	1728

Dimensioned drawing: 7870/W LED STRIP 24V DC WW 5m ROLL 19,2W/m IP20



Article Table

DESCRIPTION	Order No.
7870/W LED STRIP 24V DC WW 5m ROLL 19,2W/m IP20 LED Flexstrip, dimmable, 5 Meter Roll; 08 STRIPS & PROFILES	LID12400
Optional Accessories	
7835P LED POWER SUPPLY CABLE FOR 7825/7835/7835C/7870 10mm 08 STRIPS & PROFILES	LID14125