

Data Sheet for Article: LID13192--

Lano Quadro LED 48W 3800lm 6000K CRI80 IP20 230V 120° white

IP20, SKII, 20.000h, complete with driver



Technical Data

Luminous flux (lm)	3800
Light colour	daylight
Colour temperature (K)	6000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP20
Luminaire type	Recessed ceiling luminaire
Light source	SMD 2835
Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	79,16
Power Factor	0,9
Power (W)	48
Controller	LED driver
Operating voltage AC (V)	220-240

Technical Data - continued

Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Mounting depth (mm)	50
Colour	White
Material	Aluminum
Length (mm)	595
Width (mm)	595
Height (mm)	15
Optional Accessories	LID 13401--; LID 15037--; LID 16949--
Necessary Accessories	LID 13668--
LxWxH mm	595x595x15

Article Table

DESCRIPTION	Order No.
Lano Quadro LED 48W 3800lm 6000K CRI80 IP20 230V 120° white IP20, SKII, 20.000h, complete with driver	LID 13192
Necessary Accessories	
LED Driver, DALI & Push to dimm, 700-1400mA, 50W	LID 13668
Optional Accessories	
Suspension set for Lano, rope length 1000mm (2 piece for Lano 1200 x 600)	LID 13401
Mounting springs for panels series Lano LED, Set of 4 Pieces Not for series Lano 3 und Lano Pro	LID 15037
Through-hole quick-connector 32A, 2x L-N-PE	LID 16949