


Data Sheet for Article: LID13264--

INA-A 2 LED, 12W, 3000K, 730lm, 38°, 350mA, dimm, IP20, white **€CONOMY**




Technical Data

Cut-out size (mm)	Ø94
Luminaire type	downlight
Mounting	recessed mounting ceiling
Colour	White
Material	Aluminum
Manufacturer	06-One Light
Emission angle (°)	38
Controller	without LED Driver
Light source	COB LED
Lamp holder	LED Platine
Watt (W)	12
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	730

Technical Data - continued

Number of lamps	1
Dimmable	TRIAC
Protection class	III
IP Rating	IP20
Energy efficiency class	A
Mounting depth (mm)	120
Illuminant incl.	yes
ØxH mm	103x65
Cut-out size mm	Ø94

Dimensioned drawing: INA-A 2 LED, 12W, 3000K, 730lm,38°,350mA, dimm, IP20, white



Article Table

DESCRIPTION	Order No.
INA-A 2 LED, 12W, 3000K, 730lm,38°,350mA, dimm, IP20, white	LID13264
Optional Accessories	
LED Driver 10-15W, 350mA, Input 230V	LID12540
89012D, DRIVER 12w LED 350mA 1-10V Dimmable 100-240V	LID12538