


Data Sheet for Article: LID13468--

62130F/W/C WHITE PLAFO 30W CW IP40

230V **ECONOMY**

LED surface mounted panel; 14 PLAFO



Product Details

30W LED slim plafo light, IP40, suitable for residential and commercial application. Supplied with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.




Technical Data

Luminous flux (lm)	2550
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP40
Luminaire type	surface mounted ceiling luminaire
Illuminant incl.	yes
Number of lamps	1

Technical Data - continued

Lamp holder	LED Platine
System efficiency (lm/W)	85
Power Factor	0,9
Power (W)	30
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	1000
Input current (A)	1
Frequency (Hz)	50/60
Mounting	surface mounting ceiling
Colour	White
Material	Die-cast aluminum
Height (mm)	39
Diameter (mm)	300
Optional Accessories	LID 16949--
ØxH mm	300x39

Dimensioned drawing: 62130F/W/C WHITE PLAFO 30W CW IP40 230V



Article Table

DESCRIPTION	Order No.
62130F/W/C WHITE PLAFO 30W CW IP40 230V LED surface mounted panel; 14 PLAFO	LID13468
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949