


Data Sheet for Article: LID13538--

Sutil Quadro LED Panel 16W, 4000K, 884lm, 168x168mm, white €ECONOMY




Technical Data

Cut-out size (mm)	152x152
Luminaire type	LED Panel
Mounting	recessed mounting wall recessed mounting ceiling
Colour	White
Material	Aluminum
Cover	opal
Emission angle (°)	120
Controller	LED driver
Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Output voltage DC (V)	23-28
Output current (A)	0,50
Light source	SMD LED
Watt (W)	16

Technical Data - continued

Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
luminous flux (lm)	884
Number of lamps	1
Live time (h)	30000
Dimmable	yes with optional, dimmable driver
Appliance class	II
IP Rating	IP40
Energy efficiency class	A
illuminant incl.	yes
LxWxH mm	168x168x20
Cut-out size mm	152x152

Dimensioned drawing: Sutil Quadro LED Panel 16W, 4000K, 884lm, 168x168mm, white



Article Table

DESCRIPTION	Order No.
Sutil Quadro LED Panel 16W, 4000K, 884lm, 168x168mm, white	LID13538
Optional Accessories	
LED Driver 500mA 16W for Sutil and Plano, triac dimmable	LID13554