

Data Sheet for Article: LID13540--

Sutil-Q LED 22W 3000K 1490lm, IP40, grey

Recessed downlight, complete with driver



Technical Data

Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	Grey
Material	Aluminum
Manufacturer	O6-One Light
Beam angle (°)	120
Operating voltage AC (V)	100-240
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	22
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	1490
Number of lamps	1
Dimmable	yes with optional, dimmable driver
Protection class	II
IP Rating	IP40
Mounting depth (mm)	40

Technical Data - continued

Accessories	additional module
LxWxH mm	220x220x20

Article Table

DESCRIPTION	Order No.
Sutil-Q LED 22W 3000K 1490lm, IP40, grey Recessed downlight, complete with driver	LID13540
Optional Accessories	
89045L LED DRIVER DALI, Push, 1-10V, output 350-1100mA, 230V Adjustable output using DIP switches	LID14224
LED Driver, 1-10V & Push to dimm, 250-700mA 12-24V DC 8-16W	LID13671
89045L LED DRIVER DALI, Push, 1-10V, output 350-1100mA, 230V Adjustable output using DIP switches	LID14224