

Data Sheet for Article: LID13548--

Sutil-Q LED 30W 6000K 2174lm, IP40, grey

Recessed downlight, complete with driver



Technical Data

Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	Grey
Material	Aluminum
Manufacturer	O6-One Light
Beam angle (°)	120
Controller	LED driver
Operating voltage AC (V)	100-240
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	30
Light colour	daylight
Colour temperature (K)	6000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	2174
Number of lamps	1
Dimmable	yes with optional, dimmable driver
Protection class	II
IP Rating	IP40

Technical Data - continued

Mounting depth (mm)	40
Illuminant incl.	yes
LxWxH mm	300x300x20

Article Table

DESCRIPTION	Order No.
Sutil-Q LED 30W 6000K 2174lm, IP40, grey Recessed downlight, complete with driver	LID13548
Optional Accessories	
89045L LED DRIVER DALI, Push, 1-10V, output 350-1100mA, 230V Adjustable output using DIP switches	LID14224
LED Driver, 1-10V & Push to dimm, 250-700mA 12-24V DC 8-16W	LID13671
89045L LED DRIVER DALI, Push, 1-10V, output 350-1100mA, 230V Adjustable output using DIP switches	LID14224