


Data Sheet for Article: LID13549--

Sutil Quadro LED Panel 30W 3000K, 1957lm, 300x300mm, white **ECONOMY**




Technical Data

Cut-out size (mm)	284x284
Luminaire type	LED Panel
Mounting	recessed mounting wall recessed mounting ceiling
Colour	White
Material	Aluminum
Cover	opal
Emission angle (°)	120
Controller	LED driver
Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Output voltage DC (V)	23-28
Output current (A)	1
Light source	SMD LED
Watt (W)	30

Technical Data - continued

Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	1957
Number of lamps	1
Live time (h)	30000
Dimmable	yes with optional, dimmable driver
Protection class	II
IP Rating	IP40
Energy efficiency class	A
Illuminant incl.	yes
LxWxH mm	300x300x20
Cut-out size mm	284x284

Dimensioned drawing: Sutil Quadro LED Panel 30W 3000K, 1957lm, 300x300mm, white



Article Table

DESCRIPTION	Order No.
Sutil Quadro LED Panel 30W 3000K, 1957lm, 300x300mm, white	LID13549
Optional Accessories	
Optional dimmable LED driver for Sutil Quadro 30W	LID13556