


Data Sheet for Article: LID13844--

Sutil Round2 LED 3W 210lm 6000K CRI80

IP40 230V 120° white €ECONOMY

Recessed downlight, complete with driver




Technical Data

Luminous flux (lm)	210
Light colour	daylight
Colour temperature (K)	6000
Colour rendering index (Ra)	≥80
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP40
Luminaire type	LED Panel
Light source	SMD 2835
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	120

Technical Data - continued

System efficiency (lm/W)	70
Power Factor	0,6
Power (W)	3
Controller	LED driver
Operating voltage AC (V)	220-240
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø70
Mounting depth (mm)	50
Colour	White
Material	Acryl Plastic Die-cast aluminum
Height (mm)	22
Diameter (mm)	85
Optional Accessories	LID14224--; LID16949--
ØxH mm	85x22
Cut-out size mm	Ø70

Dimensioned drawing: Sutil Round2 LED 3W 210lm 6000K CRI80 IP40 230V 120° white



Article Table

DESCRIPTION	Order No.
Sutil Round2 LED 3W 210lm 6000K CRI80 IP40 230V 120° white Recessed downlight, complete with driver	LID13844
Optional Accessories	
89045L LED DRIVER DALI, Push, 1-10V, output 350-1100mA, 230V Adjustable output using DIP switches	LID14224
Quick connector 32A 2x3-port	LID16949