


Data Sheet for Article: LID13975--

10108FA/W/C WHITE LED 8W CW IP40

230V **ECONOMY**

complete with driver; 06 DOWNLIGHT FIX LED



Product Details

8W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 300mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.




Technical Data

Luminous flux (lm)	560
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP40
Luminaire type	LED Panel
Illuminant incl.	yes

Technical Data - continued

Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	70
Power Factor	0,6
Power (W)	8
Controller	LED driver
Operating voltage AC (V)	220-240
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 108
Mounting Depth mm (mm)	50
Colour	White
Material	Acryl Plastic Die-cast aluminum
Height (mm)	22
Diameter (mm)	120
Optional Accessories	LID 16598--
ØxH mm	120x22
Cut-out size mm	Ø 108

Dimensioned drawing: 10108FA/W/C WHITE LED 8W CW IP40 230V



Article Table

DESCRIPTION	Order No.
10108FA/W/C WHITE LED 8W CW IP40 230V complete with driver; 06 DOWNLIGHT FIX LED	LID13975
Optional Accessories	
89050TLD DALI/PUSH TO DIM/ 1-10V /TRIAC UNIVERSAL DRIVER 50W IP20 230V; 23 DRIVERS	LID16598