

Data Sheet for Article: LID13993--

Sutil Quadro2 LED 8W 560lm 840 IP40 230V 120° white **ECONOMY**

Recessed downlight, complete with driver




Technical Data

Luminous flux (lm)	560
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP40
Luminaire type	LED Panel
Light source	SMD 2835
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	120

Technical Data - continued

System efficiency (lm/W)	70
Power Factor	0,6
Power (W)	8
Controller	LED driver
Operating voltage AC (V)	220-240
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	105x105
Mounting depth (mm)	50
Colour	White
Material	Acryl Plastic Die-cast aluminum
Lenght (mm)	120
Width (mm)	120
Height (mm)	22
Optional Accessories	LID 14224--; LID 16949--
LxWxH mm	120x120x22
Cut-out size mm	105x105

Dimensioned drawing: Sutil Quadro2 LED 8W 560lm 840 IP40 230V 120° white



Article Table

DESCRIPTION	Order No.
Sutil Quadro2 LED 8W 560lm 840 IP40 230V 120° white Recessed downlight, complete with driver	LID13993
Optional Accessories	
89045L LED DRIVER DALI, Push, 1-10V, output 350-1100mA, 230V Adjustable output using DIP switches	LID14224
Quick connector 32A 2x3-port	LID16949