

Data Sheet for Article: LID13997--

Sutil Quadro2 LED 16W, 3000K, 960lm, 120°, IP40, grey €ECONOMY

Recessed downlight, complete with driver




Technical Data

Luminous flux (lm)	960
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP40
Luminaire type	LED Panel
Light source	SMD LED
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	60

Technical Data - continued

Power (W)	16
Controller	LED driver
Operating voltage AC (V)	230
Mounting	recessed mounting ceiling
Cut-out size (mm)	155x155
Mounting depth (mm)	50
Colour	Grey
Material	Aluminum
Length (mm)	173
Width (mm)	173
Height (mm)	22
Optional Accessories	LID14224--
LxWxH mm	173x173x22
Cut-out size mm	155x155

Dimensioned drawing: Sutil Quadro2 LED 16W, 3000K, 960lm, 120°, IP40, grey



Article Table

DESCRIPTION	Order No.
Sutil Quadro2 LED 16W, 3000K, 960lm, 120°, IP40, grey	LID13997
Recessed downlight, complete with driver	
Optional Accessories	
89045L LED DRIVER DALI, Push, 1-10V, output 350-1100mA, 230V	LID14224
Adjustable output using DIP switches	