

Data Sheet for Article: LID14002--

Sutil Quadro2 LED 22W, 4000K, 1540lm, 120°, IP40, grey **€ECONOMY**

LED recessed mounted panel




Technical Data

Manufacturer	06-One Light
Luminous flux (lm)	1540
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP40
Energy efficiency class	A
Luminaire type	LED Panel
Light source	SMD LED
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine

Technical Data - continued

Beam angle (°)	120
Power (W)	22
Controller	LED driver
Operating voltage AC (V)	230
Mounting	recessed mounting ceiling
Cut-out size (mm)	210x210
Mounting depth (mm)	50
Colour	Grey
Material	Aluminum
Length (mm)	225
Width (mm)	225
Height (mm)	22
Optional Accessories	LID14022--
LxWxH mm	225x225x22
Cut-out size mm	210x210
Watt (W)	22

Dimensioned drawing: Sutil Quadro2 LED 22W, 4000K, 1540lm, 120°, IP40, grey



Article Table

DESCRIPTION	Order No.
Sutil Quadro2 LED 22W, 4000K, 1540lm, 120°, IP40, grey	LID14002
LED recessed mounted panel	
Optional Accessories	
LED Driver 540mA 22W for Sutil 2, triac dimmable	LID14022