

Data Sheet for Article: LID14008--

Sutil Quadro2 LED 30W, 4000K, 2100lm, 120°, IP40, grey **ECONOMY**

Recessed downlight, complete with driver




Technical Data

Cut-out size (mm)	280x280
Luminaire type	LED Panel
Mounting	recessed mounting ceiling
Colour	Grey
Material	Aluminum
Manufacturer	06-One Light
Beam angle (°)	120
Controller	LED driver
Operating voltage AC (V)	230
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	30
Light colour	neutral white
Colour temperature (K)	4000

Technical Data - continued

Colour rendering index (Ra)	≥80
Luminous flux (lm)	2100
Number of lamps	1
Dimmable	no
Protection class	II
IP Rating	IP40
Energy efficiency class	A
Mounting depth (mm)	50
Illuminant incl.	yes
LxWxH mm	300x300x22
Cut-out size mm	280x280

Dimensioned drawing: Sutil Quadro2 LED 30W, 4000K, 2100lm, 120°, IP40, grey



Article Table

DESCRIPTION	Order No.
Sutil Quadro2 LED 30W, 4000K, 2100lm, 120°, IP40, grey	LID14008
Recessed downlight, complete with driver	
Optional Accessories	
89045L LED DRIVER DALI, Push, 1-10V, output 350-1100mA, 230V	LID14224
Adjustable output using DIP switches	