

Data Sheet for Article: LID14068--


67380A/W/W WHITE COB LED 25W WW

IP54 60d 230V **ECONOMY**

13 WALL & CEIL LED



Light distribution curve



Product Details

25W COB LED cylinder, IP54, suitable for indoor and outdoor installation. Complete with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.



Technical Data

Luminous flux (lm)	1800
--------------------	------

Technical Data - continued

Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	I
IP Rating	IP54
Luminaire type	surface mounted ceiling luminaire
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	60
System efficiency (lm/W)	72
Power Factor	0,9
Power (W)	25
Controller	LED driver
Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Operation current mA (mA)	600
Frequency (Hz)	50/60
Mounting	surface mounting ceiling
Colour	White
Material	Aluminum
Height (mm)	120
Diameter (mm)	160
Optional Accessories	LID16949--
ØxH mm	120x160

**Dimensioned drawing: 67380A/W/W WHITE COB LED 25W WW IP54 60d
230V**

Article Table

DESCRIPTION	Order No.
67380A/W/W WHITE COB LED 25W WW IP54 60d 230V 13 WALL & CEIL LED	LID14068
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949