

Data Sheet for Article: LID14382--

Noa COB LED, 12W, 700mA, 850lm, 2700K, 40°, IP20 , white

Ceiling-recessed spotlight




Technical Data

Luminous flux (lm)	850
Light colour	warm white
Colour temperature (K)	2700
Colour rendering index (Ra)	≥80
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	40
Power (W)	12
Operation current mA (mA)	700
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø87
Mounting depth (mm)	100
Colour	White

Technical Data - continued

Material	Aluminum
Height (mm)	89
Diameter (mm)	100
Optional Accessories	LID16949--
ØxH mm	100x89
Cut-out size mm	Ø87
Watt (W)	12

Dimensioned drawing: Noa COB LED, 12W, 700mA, 850lm, 2700K, 40°, IP20, white



Article Table

DESCRIPTION	Order No.
Noa COB LED, 12W, 700mA, 850lm, 2700K, 40°, IP20, white	LID14382
Ceiling-recessed spotlight	
Optional Accessories	
Through-hole quick-connector 32A, 2x L-N-PE	LID16949