


Data Sheet for Article: LID 14448--

Mercury 2 LED 12W 1100lm 830 IP20 700mA

Dimm 40° black €ECONOMY

Ceiling-recessed spotlight, dimmable



Technical Data

Luminous flux (lm)	1100
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
Light source	COB LED
Lamp holder	LED Platine
Beam angle (°)	40
System efficiency (lm/W)	91,67
Power (W)	12
Controller	Needs to be ordered separately

Technical Data - continued

Operation current mA (mA)	700
Input current (A)	0,70
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø75
Mounting depth (mm)	100
Colour	Black
Material	Aluminum
Height (mm)	96
Diameter (mm)	85
Optional Accessories	LID 14450--; LID 14453--; LID 14452--; LID 14451 --; LID 16949--
Necessary Accessories	LID 13081 --; LID 14452--; LID 14451 --;
ØxH mm	85x96
Cut-out size mm	Ø75

Dimensioned drawing: Mercury 2 LED 12W 1100lm 830 IP20 700mA Dimm 40° black



Article Table

DESCRIPTION	Order No.
Mercury 2 LED 12W 1100lm 830 IP20 700mA Dimm 40° black	LID 14448
Ceiling-recessed spotlight, dimmable	
Necessary Accessories	
LED Driver 700mA, 7-15W, Input 220-240V	LID 13081
Reflektor chrom for series Mercury 2	LID 14452
Reflektor chrom matt for Serie Mercury 2	LID 14451
Optional Accessories	
Reflektor black for Serie Mercury 2	LID 14450
Reflektor copper for Mercury 2 series	LID 14453
Reflektor chrom for series Mercury 2	LID 14452
Reflektor chrom matt for Serie Mercury 2	LID 14451
Quick connector 32A 2x3-port	LID 16949