

Data Sheet for Article: LID14669--

11107WD/W/W WHITE LED 6,5W WW 36° 700mA IP54 ADJUSTABLE

Recessed spot, requires 700mA driver; DARK LIGHT; 04 REC SPOTS ADJ LED



Product Details

6,5W LED Dark Light Recessed adjustable spot, IP54. Requires 700mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	600
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP54
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	36
System efficiency (lm/W)	92

Technical Data - continued

Power (W)	6,50
Controller	Needs to be ordered separately
Operation current mA (mA)	700
Input current (A)	0,70
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 83
Mounting depth (mm)	100
Colour	White
Material	Die-cast aluminum
Diameter (mm)	91
Optional Accessories	LID 16949--
Necessary Accessories	LID 15637--; LID 17390--
ØxH mm	90x83
Cut-out size mm	Ø 83

Dimensioned drawing: 11107WD/W/W WHITE LED 6,5W WW 36° 700mA IP54 ADJUSTABLE



Article Table

DESCRIPTION	Order No.
11107WD/W/W WHITE LED 6,5W WW 36° 700mA IP54 ADJUSTABLE Recessed spot, requires 700mA driver; DARK LIGHT; 04 REC SPOTS ADJ LED	LID14669
Necessary Accessories	
89008A DRIVER 700mA 4-8W 230V 23 DRIVERS	LID15637
89008AT DIMMABLE DRIVER 700mA 6-8W 230V 23 DRIVERS	LID17390
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949