

Data Sheet for Article: LID14744--

# Nan LED 20W 1700lm 840 IP54 220-240V white

Recessed downlight, complete with driver



## Technical Data

|                             |                           |
|-----------------------------|---------------------------|
| Luminous flux (lm)          | 1700                      |
| Light colour                | cool white                |
| Colour temperature (K)      | 4000                      |
| Colour rendering index (Ra) | ≥80                       |
| Dimmable                    | no                        |
| Protection class            | II                        |
| IP Rating                   | IP54                      |
| Illuminant incl.            | yes                       |
| Lamp holder                 | LED Platine               |
| System efficiency (lm/W)    | 85                        |
| Power Factor                | 0,9                       |
| Power (W)                   | 20                        |
| Controller                  | LED driver                |
| Operating voltage AC (V)    | 220-240                   |
| Frequency (Hz)              | 50/60                     |
| Mounting                    | recessed mounting ceiling |
| Cut-out size (mm)           | Ø166                      |

## Technical Data - continued

|                      |                   |
|----------------------|-------------------|
| Mounting depth (mm)  | 70                |
| Colour               | White             |
| Material             | Die-cast aluminum |
| Diameter (mm)        | 175               |
| Optional Accessories | LID16949--        |
| Cut-out size mm      | Ø166              |

## Dimensioned drawing: Nan LED 20W 1700lm 840 IP54 220-240V white



## Article Table

| DESCRIPTION                                                                            | Order No. |
|----------------------------------------------------------------------------------------|-----------|
| Nan LED 20W 1700lm 840 IP54 220-240V white<br>Recessed downlight, complete with driver | LID14744  |
| <b>Optional Accessories</b>                                                            |           |
| Through-hole quick-connector 32A, 2x L-N-PE                                            | LID16949  |