

Data Sheet for Article: LID14807--

10130CA/W/C WHITE 30W CW IP20 60° 230V

complete with driver; 06 DOWNLIGHT FIX LED



Product Details

30W LED recessed downlight, IP20. Ideal for general lighting applications. Complete with 750mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	2700
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥90
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP20
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	60
System efficiency (lm/W)	90

Technical Data - continued

Power Factor	0,9
Power (W)	30
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	750
Input current (A)	0,75
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 210
Mounting Depth mm (mm)	140
Colour	White
Material	Die-cast aluminum
Diameter (mm)	230
Optional Accessories	LID16949--
ØxH mm	230x110
Cut-out size mm	Ø 210

Dimensioned drawing: 10130CA/W/C WHITE 30W CW IP20 60° 230V



Article Table

DESCRIPTION	Order No.
10130CA/W/C WHITE 30W CW IP20 60° 230V complete with driver; 06 DOWNLIGHT FIX LED	LID14807
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949