

Data Sheet for Article: LID14848--

10112TP/B/W BLACK COB 12W WW IP65

DARK LIGHT 700mA

Recessed spot, quick fix, requires 700mA driver; 02 REC SPOTS FIX LED



Product Details

12W COB LED recessed spot, IP65, for general application. Suitable for bathroom installation. Requires 700mA constant current driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	1100
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP65
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	38
System efficiency (lm/W)	91

Technical Data - continued

Power (W)	12
Controller	Needs to be ordered separately
Operation current mA (mA)	700
Input current (A)	0,70
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 75
Mounting Depth mm (mm)	110
Colour	Black
Material	Die-cast aluminum
Diameter (mm)	83
Optional Accessories	LID16949--
Necessary Accessories	LID13081--;
ØxH mm	82x100
Cut-out size mm	Ø 75

Dimensioned drawing: 10112TP/B/W BLACK COB 12W WW IP65 DARK LIGHT 700mA



Article Table

DESCRIPTION	Order No.
10112TP/B/W BLACK COB 12W WW IP65 DARK LIGHT 700mA Recessed spot, quick fix, requires 700mA driver; 02 REC SPOTS FIX LED	LID14848
Necessary Accessories	
89015A DRIVER 700mA 7-15W 230V 23 DRIVERS	LID13081
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949