

Data Sheet for Article: LID14852--

10112FA/B/C BLACK LED 12W CW IP40 230V

complete with driver; 06 DOWNLIGHT FIX LED



Product Details

12W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 250mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	840
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP40
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	70
Power Factor	0,9
Power (W)	12
Controller	LED driver

Technical Data - continued

Operating voltage AC (V)	220-240
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 155
Mounting Depth mm (mm)	50
Colour	Black
Material	Acryl Plastic Die-cast aluminum
Diameter (mm)	173
Optional Accessories	LID16949--
Cut-out size mm	Ø 155

Dimensioned drawing: 10112FA/B/C BLACK LED 12W CW IP40 230V



Article Table

DESCRIPTION	Order No.
10112FA/B/C BLACK LED 12W CW IP40 230V complete with driver; 06 DOWNLIGHT FIX LED	LID14852
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949