


Data Sheet for Article: LID15010--

11104K/B/W BLACK 3W@350mA 5W@500mA WW ADJUSTABLE DARK LIGHT

quick fix Ring must be ordered separately requires 350-500mA driver; 04 REC SPOTS ADJ LED



Product Details

4W COB LED adjustable recessed spot with interchangeable rings. Ring must be ordered separately. Requires 350/500mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	400
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	35

Technical Data - continued

System efficiency (lm/W)	80
Power (W)	3;5
Controller	Needs to be ordered separately
Operation current mA (mA)	350/500
Input current (A)	0,35/0,5
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 60
Mounting Depth mm (mm)	80
Colour	Black
Material	Aluminum
Diameter (mm)	68
Optional Accessories	LID 16949--
Necessary Accessories	LID 15012--; LID 15015--; LID 15014--; LID 15013--; LID 13677--; LID 16462--;
ØxH mm	68x62
Cut-out size mm	Ø 60

Article Table

DESCRIPTION	Order No.
11104K/B/W BLACK 3W@350mA 5W@500mA WW ADJUSTABLE DARK LIGHT quick fix Ring must be ordered separately requires 350-500mA driver; 04 REC SPOTS ADJ LED	LID15010
Necessary Accessories	
050100/B BLACK RING FOR 11104K 04 REC SPOTS ADJ LED	LID15012
050100/BS BRASS RING FOR 11104K 04 REC SPOTS ADJ LED	LID15015
050100/C CHROME RING FOR 11104K 04 REC SPOTS ADJ LED	LID15014
050100/CU COPPER RING FOR 11104K 04 REC SPOTS ADJ LED	LID15013
89004 DRIVER 350mA 1-4W IP66 230V 23 DRIVERS	LID13677
89004T DIMMABLE DRIVER 350mA 2-4W IP66 230V 23 DRIVERS	LID16462
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949